UL Product iQ®

Wiring, Printed - Component

COMPANY

AKA PCB D O O
Rozna Dolina 54
Lesce, 4248 Slovenia

E208099

Type	Cond Width Min mm	Min Edge mm	Cond Thk mic	SS/ DS/ DSO	Max Area Diam mm	Report date After 2022-01-01	Surface Mount Technology	Assembly Solder Process Temp °C	Solder Process Cycles	Solder Limits °C	Solder Limits sec	Max Oper Temp °C	Flame Class	Meets UL796 DSR	C T I
Single layer metal base printed wiring boards															
4	0.10	0.10	35	SS	30.0	No	-	-	-	260	10	130	V-0	All	0
5 (ASP 1)	0.10	0.10	35	SS	30	Yes	Yes	260	3	-	-	130	V-0	All	0
Single layer printed wiring boards															
3	0.18	0.25	33	SS	20.6	No	-	-	-	270	10	130	V-0	All	*
6 (ASP 1)	0.10	0.10	33	SS	30.0	Yes	Yes	260	3	270	10	130	V-0	All	*

* - CTI marking is optional and may be marked on the printed wiring board.

ASP 1 - Assembly solder process evaluated to IPC-TM-650, 2.6.27 Thermal Stress Assembly Simulation.

Marking: Company name or trademark 

or file number and type designation. May be followed by a suffix to denote factory identification or flammability classification..

Last Updated on 2025-09-29

UL Product iQ®

Wiring, Printed Certified for Canada - Component

COMPANY

AKA PCB D O O
Rozna Dolina 54
Lesce, 4248 Slovenia

E208099

Type	Cond Width Min mm	Min Edge mm	Cond Thk mic	SS/ DS/ DSO	Max Area Diam mm	Report date After 2022-01-01	Surface Mount Technology	Assembly Solder Process Temp °C	Solder Process Cycles	Solder Limits °C	sec	Max Oper Temp °C	Flame Class	Meets UL796 DSR	C T I
Single layer metal base printed wiring boards															
4	0.10	0.10	35	SS	30.0	No	-	-	-	260	10	130	V-0	All	0
5 (ASP 1)	0.10	0.10	35	SS	30	Yes	Yes	260	3	-	-	130	V-0	All	0
Single layer printed wiring boards															
3	0.18	0.25	33	SS	20.6	No	-	-	-	270	10	130	V-0	All	*
6 (ASP 1)	0.10	0.10	33	SS	30.0	Yes	Yes	260	3	270	10	130	V-0	All	*

* - CTI marking is optional and may be marked on the printed wiring board.

ASP 1 - Assembly solder process evaluated to IPC-TM-650, 2.6.27 Thermal Stress Assembly Simulation.

Marking: Company name or trademark AKA or file number and type designation and the Recognized Component Mark for Canada, c UL us. May be followed by a suffix to denote factory identification or flammability classification..

Last Updated on 2025-09-29

and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.